

GPR SERIES

PERKINS Powered
Diesel Generator

GENPOWER®

GENERATOR

GPR 1125

Engine Speed rpm	Frequency Hz	Type of Operations	Genset Power		Engine Power (Net)	
			kVA	kW	kWm	bbh
1500	50	Prime Power	1030	824	861	1155
		Standby Power	1125	900	947	1270

STANDARD SPECIFICATIONS

Engine

- PERKINS Heavy duty diesel engine
- Revolution: 1500 rpm
- Water cooled
- Tropical type radiator

Alternator

- VDE 0530 & IEC 34-1 standardizations
- Synchron type brushless
- Automatic voltage regulation (AVR)
- Overload acceptance: 110% for 1 hour, 150% for 2 minutes
- Short circuit resistance: 300 for 10 seconds
- Insulation class: H
- Insulation resistance: 1800 VAC
- Voltage: 230/400 V
- Voltage regulation: $\pm 0,5\%$
- Protection class: IP23
- Power factor (cosq): 0,8
- Frequency: 50 Hz

Manuel Control Panel

- Microprocessed Electronic Control Panel
- Relays
- Protection fuses
- Thermic magnetic circuit breaker (TMS) 3-pole
- Emergency stop button

Automatic Control Panel

- Microprocessed AMF Electronic Control Panel
- Protection fuses
- Battery charger
- Power Transfer (For ATS)
- Emergency stop button

Chassis

- Mounted on the steel base chassis
- Elastic vibration dampers between engine and chassis
- Chassis integrated fuel tank
- Dial type mechanical fuel indicator

Canopy

- Easy lifting and moving
- Metal parts are coated with electrostatic polyester coated, powder painted
- Thermally insulated exhaust system
- Acoustic insulation with rot*proof, moisture-repellent and non-flammable material (per DIN 4102 A2)



ENGINE

Make	PERKINS
Model	4008TAG2A
Number of Cylinder	8
Cylinder arrangement	In-line
Cycle	4 stroke
Aspiration	Turbocharged AAC*
Combustion system	Direct injection
Compression ratio	13.6:1
Bore and Stroke	mm 160 x 190
Displacement	lt 30,561
Cooling System	Water Cooled
Total coolant capacity	lt 162
Total lubrication	lt 153
Governor Type	Electronic
Electric System	24 VDC

Fuel Consumption %50 Loaded	lt/h 108
Fuel Consumption %75 Loaded	lt/h 160
Fuel Consumption % 100 Loaded	lt/h 215
Fuel Tank Cap.	lt 1500

DIMENSIONS

Width w/o Canopy (w/canopy)	mm 2040 (2438)
Lenght w/o Canopy (w/canopy)	mm 4470 (6060)
Height w/o Canopy (w/canopy)	mm 2400 (3000)
Weight w/o Canopy (w/canopy)	kg 7820 (11920)

TECHNICAL SPECIFICATIONS